

US009410996B2

US 9,410,996 B2

Aug. 9, 2016

# (12) United States Patent Du et al.

## (54) METHOD AND SYSTEM EMPLOYING FINITE STATE MACHINE MODELING TO IDENTIFY ONE OF A PLURALITY OF DIFFERENT ELECTRIC LOAD TYPES

(71) Applicants: **EATON CORPORATION**, Cleveland, OH (US); **GEORGIA TECH RESEARCH CORPORATION**,

Atlanta, GA (US)

(72) Inventors: Liang Du, Atlanta, GA (US); Yi Yang, Milwaukee, WI (US); Ronald Gordon

Harley, Lawrenceville, GA (US); Thomas G. Habetler, Snellville, GA (US); Dawei He, Beijing (CN)

(73) Assignee: EATON CORPORATION, Cleveland,

OH (US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 562 days.

(21) Appl. No.: 13/908,263

(22) Filed: **Jun. 3, 2013** 

(65) **Prior Publication Data** 

US 2014/0358456 A1 Dec. 4, 2014

(51) Int. Cl.

 G01R 21/06
 (2006.01)

 G01R 19/00
 (2006.01)

 G01D 4/00
 (2006.01)

(52) U.S. Cl.

(58) Field of Classification Search

CPC ....... G06N 3/088; G01D 4/004; G01R 19/00; G01R 21/06; Y04S 20/38

USPC ............. 702/60, 64; 323/273; 324/76.12, 521; 361/78; 707/737, 748, 757

See application file for complete search history.

(10) **Patent No.:** 

(56)

(45) **Date of Patent:** 

## References Cited U.S. PATENT DOCUMENTS

4,858,141 A 8/1989 Hart et al. 5,483,153 A 1/1996 Leeb et al. (Continued)

### FOREIGN PATENT DOCUMENTS

GB	2465367 A	5/2010
WO	2006/067665 A1	6/2006
WO	2010/005985 A1	1/2010

### OTHER PUBLICATIONS

European Patent Office, "International Search Report and Written Opinion", Sep. 19, 2014, 9 pp.

A. Bouloutas et al., "Fault Identification Using a Finite State Machine Model with Unreliable Partially Observed Data Sequences", IEEE Transactions on Communications, vol. 41, No. 7, Jul. 1993, pp. 1074-1083.

(Continued)

Primary Examiner — John H Le

(74) Attorney, Agent, or Firm — Eckert Seamans Cherin & Mellott, LLC; Grant E. Coffield; Nathaniel C. Wilks

### (57) ABSTRACT

A system is for a plurality of different electric load types. The system includes a plurality of sensors structured to sense a voltage signal and a current signal for each of the different electric loads; and a processor. The processor acquires a voltage and current waveform from the sensors for a corresponding one of the different electric load types; calculates a power or current RMS profile of the waveform; quantizes the power or current RMS profile into a set of quantized state-values; evaluates a state-duration for each of the quantized state-values; evaluates a plurality of state-types based on the power or current RMS profile and the quantized state-values; generates a state-sequence that describes a corresponding finite state machine model of a generalized load start-up or transient profile for the corresponding electric load type; and identifies the corresponding electric load type.

### 24 Claims, 15 Drawing Sheets

